


FOZAR

Linear LED lighting



 ideelight


www.ideelight.lt



FOZAR


UGR
<19

RoHS



| CODE | POWER | CCT | LUMINOUS FLUX | LENGTH |
|--------------------|-------|-------|---------------|---------|
| 420580154090010203 | 15W | 4000K | 1997lm | 580 mm |
| 420860234090010203 | 23W | 4000K | 2996lm | 860 mm |
| 421140314090010203 | 31W | 4000K | 3995lm | 1140 mm |
| 421420384090010203 | 38W | 4000K | 4993lm | 1420 mm |
| 421700464090010203 | 46W | 4000K | 5992lm | 1700 mm |
| 421980544090010203 | 54W | 4000K | 6991lm | 1980 mm |

CODE GENERATION



| Series | Type | Length | Power | CCT | CRI | Diffuser 1 | Diffuser 2 | Control | IP | Colour | | | | | | | | | | | |
|--------|------|-----------|-------|------------|-----|------------|------------|------------|----|--------|----|------|---|-------------|---|---------|---|----|----|------------|---|
| 3880 | 4 | surface | 1 | 580mm | 058 | 15w | 015 | 3000k | 30 | 80 | 80 | none | 0 | MPRM | 1 | none | 0 | 20 | 20 | white | 1 |
| 5080 | 5 | suspended | 2 | 860mm | 086 | 23w | 023 | 4000k | 40 | 90 | 90 | MPRM | 1 | OPAL | 2 | NFC | 1 | 44 | 44 | grey | 2 |
| 6890 | 7 | recessed | 3 | 1140mm | 114 | 31w | 031 | 5000k | 50 | | | OPAL | 2 | Honey black | 3 | 0/1-10V | 2 | | | black | 3 |
| | | | | 1420mm | 142 | 38w | 038 | 6500k | 65 | | | | | Line black | 4 | DALI | 3 | | | on request | 0 |
| | | | | 1700mm | 170 | 46w | 046 | 2700-6500k | 26 | | | | | Honey white | 5 | Dimmer | 4 | | | | |
| | | | | 1980mm | 198 | 54w | 054 | | | | | | | Line white | 6 | | | | | | |
| | | | | on request | 000 | on request | 000 | | | | | | | | | | | | | | |


ideelight

www.ideelight.lt

FOZAR

Features and options


- * Health oriented comfort light UGR<19
- * Wide range combinations of reflectors and diffusers for supreme comfort: opal+prism, prism+cell etc.



- * EU components, guarantee 5 years
- * 0/1-10V, NFC, DALI dimming on request
- * Low ripple current <1%
- * Power factor at full load >0,97
- * Overload and over-temperature protection
- * Protection against "no load" operation
- * Electronic short-circuit
- * Easy service access


- * polymer powder painted aluminium
- * RAL colour on request from 1pc
- * IP44 protection as option

Mechanical dimmer
0-100% installed on request




- * EU components, guarantee 5 years
- * Efficiency: up to 211 lm/W
- * Lifetime 78000h (L80, B10)
- * CRI 90
- * 2700-6500K tunable light on request

Dimension series




Mounting types



FOZAR

Customization



- * Wide variety of forms with different angles and lengths on request
- * Easy movable suspensions and custom power-in positions
- * No light gaps on corners and connections

